

MATERIAL SAFETY DATA SHEET

Reference No		WTX19S11082534B003
Applicant	:	SYSMAX Innovations Co., Ltd.
Address	1	Rm 2601-06, Central Tower, NO.5 Xiancun Road, Tianhe District, Guangzhou, 510623, Guangdong, China
Manufacturer		Sysmax Power Technology.LLC
Address	:	B4 Happy Factory, 81 East Huahong Commercial Street, North Zhenxing Road, Gaobu Dongguan, China
Sample's name	÷	Power station
Date of Issue	•	2020-03-12

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F, Fukangtai Building, West Baima Rd., Songgang Street, Baoan District,

Shenzhen Guangdong, China

Tel:+86-755-83551033

Fax:+86-755-83552400

Compiled by:

iu

Jeff Liu / Project Engineer

Approved by:



Philo Zhong / Manager

Material Safety Data Sheet


Page 2 of 7

Section 1-Chemical Product and Company Identification

Product Name:	Power station
Model No.:	NPS400
Ratings	10.8V, 39Ah, 421Wh
Weight:	Approx. 5.68Kg
Manufacturer:	Sysmax Power Technology.LLC
Address:	B4 Happy Factory, 81 East Huahong Commercial Street, North Zhenxing Road, Gaobu Dongguan, China
Emergency Telephone:	0769-82660898
Fax:	0769-82690896
Email:	525874853@qq.com

Section 2-Hazards Identification

Classification:	Not dangerous with normal use. Do not dismantle、open or shred battery. The hazards indicated are for a ruptured battery. Exposure to the ingredients contained within or their ingredients products could be harmful.
Appearance, Color and odor	Solid object with no odor, no color.
Invasion route:	ACUTE : see Section 8 for exposure controls In the event that this battery has been ruptured, the electrolyte solution contained within the battery would be corrosive and can cause burns.
	Skin contact: The leakage of the electrolyte may cause sore and stimulation on the skin
	Eye contact : The steam of the electrolyte may stimulate eyes. Especially, substance that may cause inflammation of the eyes is contained
	Inhalation: Inhalation of materials from a sealed battery is not an expected route of exposure. Vapors or mists from a ruptured battery may cause respiratory irritation.
	Ingestion: Swallowing is not anticipated due to the battery size. The ingestion of the electrolyte causes tissue damage to throat
Health hazards:	For the battery or cell, chemical materials are stored in a sealed metal or metal laminated plastic case, which designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there is no physical danger of ignition, explosion or leakage of hazardous materials. However, if exposed to a fire, added mechanical shocks or decomposed, these improper handlings would cause the leakage of electrolyte. Moreover, if heated strongly by the surrounding fire, acrid gas may be emitted
Environment	Electrolyte leakage or battery container rupture may lead to the leakage of inner
hazards:	component into the environment
Burn & burst	Do not dispose of battery in firemay explode. Do not short-circuit the battery-
danger:	may cause fire



Page 3 of 7

Section 3 – Composition/information on Ingredient

Pure Admixture

Chemical Composition	Molecular Formula	CAS No.	Weight(%)
Lithium Cobalt Oxide	LiCoO ₂	12190-79-3	36
Aluminum	AI	7429-90-5	8
Graphite	С	7782-42-5	15
Copper	Cu	7440-50-8	10
Phosphate(1-), hexafluoro-, lithium	N/A	21324-40-3	10
Ethylene carbonate	N/A	96-49-1	9
Other	N/A	N/A	12

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Section 4 – First Aid Measure

Skin touch:	Remove all contaminated clothing and flush extraneous matter with soap and plenty of water immediately for at least 15 minutes. Get medical aid.
Eyes touch:	In case of contact electrolyte with eyes, rinse immediately with plenty of water. Have the victims remove contact lenses if he is wearing them before rinsing. Do not let the victims rub his eyes. Get medical aid.
Inhalation:	Remove to fresh air. Give oxygen or artificial respiration if needed. Get medical aid.
Ingestion:	Swallowing is not anticipated in normal condition. If accidentally eat the product, dilute by giving plenty of water and get medical aid. Assure that mucus does not obstruct the airway. Do not give anything by mouth to an unconscious person

Section 5 – Fire Fighting measures

Danger	Non-flammable. The batteries can leak combustible electrolyte fumes in case of over
characteristic:	heat resulting from inappropriate use.
Hazardous combustion	Irritant gas may be emitted if burned or exposed to fire
products:	
Hazardous	
combustion	Irritant gas may be emitted if burned or exposed to fire
products:	
Fire-Fighting method & media:	The staff must equipped with filter mask (full mask) or isolated breathing apparatus. The staff must wear the clothes and gloves which can defend the fire and the toxic gas. When the battery burns with other combustibles simultaneously, take fire-extinguishing method which correspond to the combustibles. Extinguish a fire from the windward as much as possible
Extinguishant:	Carbon dioxide, dry chemical, foam, etc



Reference No: WTX19S11082534B003

Page 4 of 7



Section 6 – Accidental Release Measures

Personal precautions	Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
Other Information	Refer to protective measures listed in section 7 and 8.
Environmental precautions	Refer to protective measures listed in Section 7 and 8. Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.
Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Pick up and transfer to properly labeled containers.

Section 7 – Handing and storage

Handing:	Before handling the batteries, the users should read the product specification carefully. Do not crush, pierce the battery terminals with conductive goods. Not directly heat or solder. Do not throw in fire. Do not mix batteries of different types. Do not mix new and used batteries. Keep batteries in non-conductive trays
Storage:	Store batteries in cool and ventilated area away from sources of heat, open flames, corrosive chemicals, food and drink. Since short circuit can cause burn, leakage and rupture, keep batteries in original packaging until use and do not jumble them. Keep away form children

Section 8 – Exposure controls, Personal Protection

Maximum admissible	No information is available
concentration:	
Monitoring Method:	Use ventilation or other monitoring devices to control temperature, humidity and fumes
Engineering Control:	Use ventilation or other monitoring devices to control temperature, humidity and fumes
Respiratory Protection:	Not necessary under normal use. In case of battery rupture, use self-contained respiratory equipment
Eyes/face Protection:	Not necessary under normal use. Wear safety goggles if handing a leaking or ruptured batteries
Skin and Body protection:	Not necessary under normal use. Use rubber apron and protective clothes in case of handing a leaking or ruptured batteries
Hands Protection:	Not necessary under normal use. Use rubber gloves if handing a leaking or ruptured batteries
Hygiene Measures:	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Contaminate work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use.
Other Protections:	None



Page 5 of 7

Physical state:	Solid
Color:	Black
Odor:	No information is available
pH Value:	Not available
Boiling point	
/range	Not available
Melting /freezing	
Point:	Not available
Flash point:	Not available
Evaporation	
rate:	Not available
Upper	
flammable(explo	
sive) limits in air-	Not available
Lower (vol%)-	
UEL:	
Vapor pressure:	Not available
Vapor density:	Not available
Specific Gravity:	Not available
Water Solubility:	Immiscible in water
Solubility in	Not available
other solvents:	Not available
Partition	
coefficient (n-	Not available
octanol / water):	
Autoignition	Not available
temperature	
Decomposition	Not available
temperature:	
Kinematic	Not available
viscosity:	
Dynamic	Not available
viscosity:	
Explosive	Not available
properties:	
Oxidizing	Not available
properties:	
Evaporation	Not available
rate:	
Ignition	No information is available
temperature:	
Any addition information:	None
information:	

Section 9 – Physical and Chemical Properties



Section 10 – Stability and Reactivity

Page 6 of 7

Reactivity:	No data is available
Chemical	Stable under recommended storage condition
stability:	
Possibility of	None under normal processing.
Hazardous	
Reactions:	
Hazardous	No information is available
Polymerization:	
Conditions to	Exposure to air or moisture over prolonged periods.
avoid:	
Incompatible	Acids, Bases, Oxidizing agent.
materials	
Hazardous	Irritant gas may be emitted if burned or exposed to fire
Decomposition	
Products:	

Section 11 – Toxicological Information

Acute Toxicity:	No information is available
Sub-acute and	Lithium ion batteries do not contain toxic materials
Chronic Toxicity:	
Irritation:	Irritation only occurs if the batteries are abused and it may cause irritation to skin,
	eyes, respiratory tract.
Sensitization:	No information is available
Mutagenicity:	No information is available
Carcinogenicity:	No information is available
Others:	None

Section 12 – Ecological Information

Eco-toxicity:	When properly used and disposed, lithium iron batteries do not present environment
	hazard
Biodegradable:	No information is available
Non-	No information is available
biodegradable:	
Bioconcentration	No information is available
or biological	
accumulation:	
Other harmful	None
effects:	

Section 13 – Disposal Considerations

Nature of waste:	No information is available
Waste disposal methods:	Dispose in accordance with applicable regulations which vary from country to country. In more countries the discard of used batteries is forbidden and the end-users are invited to dispose them properly. Lithium ion battery should have their terminals insulated and be preferably wrapped in plastic bags prior to disposal
Contaminated Packaging:	Dispose of contents/containers in accordance with local regulations.
Attention abandoned:	Incineration should never be performed by battery user

Waltek Services (Shenzhen) Co., Ltd. http://www.waltek.com.cn

Page 7 of 7



Section 14 - Transport information

Note:	This report applies to transportation of by air、by sea and by land.
	The Power station NPS400 has passed the test Section 38.3 of Recommendations on
	the Transport of Dangerous Goods, Manual of Test and Criteria. Report No.: WTX19S11082534B001
	The transportation of lithium cells and batteries is regulated by the International Civil
	Aviation Organization, International Air Transport Association, International Maritime
	Dangerous Goods Code.
	Package according to packing instruction 965~967 of IATA DGR 61st Edition for transportation.
	When shipped by sea, package should according to packing instruction P903of IMDG CODE 39-18 Edition for transportation.
	When shipped by road, package should according to packing instruction P903 of ADR
	2019 Edition for transportation.
UN Number:	3480/3481
Class:	1
Packing group:	I
Proper shipping	Lithium-ion batteries shipping along with equipment/ Lithium-ion batteries shipping
name:	singly/ Lithium-ion batteries contained in equipment
Packaging Mark:	Each package must be labeled with a lithium battery label.
Packaging	No information is available
Method:	
Transport	By air /By sea
Fashion:	
	Examine whether the package of the containers are integrate and tight-closed or not
Transport	before transport. No divulgence, no collapse, no precipitation or no damage during
Attentions:	the course of transportation. Don't put the goods together with corrosive chemicals. Stopovers should be away from fire and heat sources

Section 15 – Regulatory Information

Regulatory	ISO 11014-2009 Safety data sheet for chemical products – Content and order of
Information:	sections.
	GB/T 16483-2008 Safety data sheet for chemical products – Content and order of
	sections The international Maritime Dangerous Goods (IMDG) Code
	International Air Transport Association (IATA) Dangerous Goods Regulations, 61st,
	2020
	The European Agreement concerning the International Carriage of Dangerous
	Goods by Road (ADR)
	The Regulations Concerning the International Transport of Dangerous Goods by
	Rail (RID)
	U.S. Department of Transportation (DOT)
	Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Section 16 – Additional Information

Information: Information: The above information is based on the data of which we are aware and is believed be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the result of its use. This information is furnished upon condition that the person receiving it shall make here own determination of the suitability of the material for this particular purpose

===== End of Report ======